

WHOLESALE SMS GATEWAY (SMPP v3.4) INTERCONNECTION SPECIFICATION

Trust | Service | Relationship — Registered Office: 87–105 Chatham Road, Tsim Sha Tsui, Kowloon, Hong Kong

1. CORPORATE & OPERATIONS ESCALATION MATRIX

Legal Entity Name:	AVM Networks Limited (Hong Kong CR No: 3181853)
Corporate Headquarters:	Room 409, Beverley Commercial Centre, 87–105 Chatham Road, Tsim Sha Tsui, Hong Kong
Official Website / Phone:	https://avmnetworkslimited.com Corporate Switchboard: +44 20 4577 3300
24/7 Technical NOC Email:	noc@avmnetworkslimited.com (Whitelisting, SMPP Binds, DLR Audits)
Carrier Commercial & Rates:	sales@avmnetworkslimited.com (Bilateral Volume, Price Lists, Commercial Terms)
Bilateral Billing & Finance:	billing@avmnetworkslimited.com (Invoicing, CDR Reconciliation, Credit Settlement)

2. AVM NETWORKS SMPP v3.4 GATEWAY SPECIFICATIONS

Primary SMPP Gateway Host / IP:	178.18.243.45 (DNS: smpp.avmnetworkslimited.com)
SMPP Service Port:	2775 (Standard Wholesale) TLS Port: 3775 (Secure Enterprise)
Supported Bind Modes:	Transceiver (TRX), Transmitter (TX), Receiver (RX) [Up to 10 Binds per account]
Default Throughput & System Type:	100 TPS Default (Expandable up to 500+ TPS) System Type: "smpp" or Blank
Character Encodings:	GSM 7-bit (0x00), UCS-2 Unicode (0x08), Latin 1 / ISO-8859-1 (0x03), UTF-8
Delivery Receipts (DLR):	Full DLR Lifecycle Delivered via Deliver_SM (UTC Timezone / ISO 8601)
Destination MSISDN Format:	Standard International E.164 without leading "+" (e.g. 447123456789, 12125550199)
Sender ID / CLI Preservation:	Alphanumeric (TON:5, NPI:0) & International Numeric (TON:1, NPI:1) Supported
Security & Whitelisting Policy:	Strict Bi-directional Public IP Firewall Whitelisting mandatory before account activation

3. PARTNER INTERCONNECTION DETAILS (FILL & RETURN TO noc@avmnetworkspostal.com)

Partner Legal Company Name:			
Partner Country & Tax / CR ID:			
24/7 Operations / NOC Email:		NOC Phone:	
Commercial / Account Manager:		Skype/Teams:	
Partner Public IP(s) to Whitelist:	(Port / Bind:)		
Preferred Bind Mode & TPS:	[] Transceiver (TRX) [] TX & RX Pair	Expected TPS:	
Sample Test Mobile Numbers:	1)	2)	
Authorized Signatory & Date:	Name:	Signature:	